

# General Options

## General Options

There are many options that most customers choose with their machine such as the misting system or the dust collector attachment, but there are also a lot of specialty options for different work environments or production requirements. As an example of options for specific work environments, options such as stainless steel racks, and air conditioning for the control enclosure are really only going to be a consideration to customers in a very hot, humid climate.

The following pages review the upgrades, aggregates, boring heads, saws and accessories that are available to customize your FlexiCAM to your specifications.

Floating Z Axis, CNC Rotary Axis, Saw/Double Horizontal Drill & ATC Spindle

## Upgrades

These are upgrades available to your machine at time of order or at a later date.

### Bar code Scanner

Designed to simplify operation of the FlexiCAM, it integrates with most popular CAM packages and is included standard with the PRO NBM Configuration

### Automatic Central Bearing Lubrification

Recommended for solid surface, woodworking or other applications where abrasive materials are used Grease based lubricant is used rather than an oil type, to avoid dripping

### CNC Rotary Axis

Incl. manual tailstock, 3 jaws chuck diameter 100mm/4";, Servo motor & drive, controller card Requires the FlexiCAM ACS Control

Add 3" to Z clearance - Upgrade from 8" clearance to 11";

Recommended for use with aggregate tooling Clearance is measured between bottom of gantry and table top

Add 7" to Z clearance - Upgrade from 8" clearance to 15";

Clearance is measured between bottom of gantry and table top

### Additional Carriage - Stealth

Includes additional individual Y Axis motor

### Additional Carriage - XL

Includes additional individual Y Axis motor

### Additional Carriage (carriage can remain in PARK if not needed) - Cobra

Additional Y and Z Axis motors, spacing is controlled by software. The main application is tandem cutting of parts with variable tool spacing

### Extended Gantry - 2 carriages

With the extended gantry, each carriage can cover the complete working area

### Extended Gantry - 3 carriages

With the extended gantry, each carriage can cover the complete working area

### Wide carriage for 2 or 3 spindles

Main application is the tandem cutting of parts with variable tool spacing 2 or 3 spindles are mounted to the same carriage, distance has be adjusted manually maximum distance between the outer spindles is 750mm

**Network Surge Protector**

Protect your controller against powers outs and power surges.

**Stainless Steel Linear Bearings Upgrade**

Price and availability vary for each series and size of machine

**Stainless Steel Linear Bearings Carts Upgrade**

Price and availability vary for each series and size of machine

**Stainless Steel Rack & Pinion Upgrade**

Price and availability vary for each series and size of machine